



**Art. 014-1079-000**

Grease control gun without pipe and coupling

Inlet F 1/4"

014-1079-000



**Art. 014-1080-000**

Grease control gun with flexible hose and 4-jaws coupling

Length flexible hose: 400 mm

Thread inlet F 1/4"

014-1080-000



**Art. 014-1081-000**

Grease control gun with flexible hose and 4-jaws coupling

Length flexible hose: 400 mm

Swivelling joint F 1/4"

014-1081-000



**Art. 014-1081-010**

Grease control gun with flexible hose and 4-jaws coupling

Length flexible hose: 400 mm

Triple-swivelling joint F 1/4"

014-1081-010



**Art. 014-1082-000**

Grease control gun with rigid pipe and 4-jaws coupling

Length rigid pipe: 200 mm

Swivelling joint F 1/4"

014-1082-000



**Art. 014-1083-000**

Grease control gun with rigid pipe and 4-jaws coupling

Length rigid pipe: 200 mm

Swivelling joint F 1/4"

014-1083-000



**Art. 014-1083-010**

Grease control gun with rigid pipe and 4-jaws coupling

Length rigid pipe: 200 mm

Triple-swivelling joint F 1/4"

014-1083-010

All grease guns are supplied for the connection of the swivelling joint Art.014-1091-000 or the triple-swivelling joint Art.014-1090-000

## Art. 014-1079-003

Grease control gun without pipe and coupling  
Inlet **F 3/8"**



014-1079-003

## Art. 014-1080-003

Grease control gun with flexible hose and 4-jaws coupling  
Length flexible hose: 400 mm  
Thread inlet **F 3/8"**



014-1080-003

## Art. 014-1081-003

Grease control gun with flexible hose and 4-jaws coupling  
Length flexible hose: 400 mm  
Swivelling joint **F 3/8"**



014-1081-003

## Art. 014-1081-013

Grease control gun with flexible hose and 4-jaws coupling  
Length flexible hose: 400 mm  
Triple-swivelling joint **F 3/8"**



014-1081-013

## Art. 014-1082-003

Grease control gun with rigid pipe and 4-jaws coupling  
Length rigid pipe: 200 mm  
Swivelling joint **F 3/8"**



014-1082-003

## Art. 014-1083-003

Grease control gun with rigid pipe and 4-jaws coupling  
Length rigid pipe: 200 mm  
Swivelling joint **F 3/8"**



014-1083-003

## Art. 014-1083-013

Grease control gun with rigid pipe and 4-jaws coupling  
Length rigid pipe: 200 mm  
Triple-swivelling joint **F 3/8"**



014-1083-013

All grease guns are supplied for the connection of the swivelling joint Art.014-1091-003 or the triple-swivelling joint Art.014-1090-003



**014-1081-S10**

**Art. 014-1081-S10**

Gun with lever protection, flexible hose and 4-jaws coupling

Flexible hose lenght: 400 mm

Triple-swivelling joint **F 1/4"**



**014-1081-S13**

**Art. 014-1081-S13**

Gun with lever protection, flexible hose and 4-jaws coupling

Flexible hose lenght: 400mm

Triple-swivelling joint **F 3/8"**



**014-1083-S10**

**Art. 014-1083-S10**

Gun with lever protection, rigid hose and 4-jaws coupling

Rigid hose lenght: 200 mm

Triple-swivelling joint **F 1/4"**



**014-1083-S13**

**Art. 014-1083-S13**

Gun with lever protection, rigid hose and 4-jaws coupling

Rigid hose lenght: 200 mm

Triple-swivelling joint **F 3/8"**



**014-1090-000**

**Art. 014-1090-000**

Triple-swivelling joint **M-F 1/4 "**

**Art. 014-1090-003**

Triple-swivelling joint **M-F 3/8 "**



**014-1091-000**

**Art. 014-1091-000**

Straight swivelling joint **M-F 1/4 "**

**Art. 014-1091-003**

Straight swivelling joint **M-F 3/8 "**



**014-1085-000**

**Art. 014-1085-000**

Flexible hose lenght 400 mm

Thread M 10x1 mm



**014-1086-000**

**Art. 014-1086-000**

Rigid hose lenght 200 mm

Thread M 10x1 mm

## Art. 014-1084-000

### Grease digital meter K200

Equipped with two displays, one is for batch counting (can be put to zero) and the other one for total volumes (cannot be put to zero) of the dispensed grease.



014-1084-000

## Art. 014-1084-010

### Grease digital meter K200 HP PULSER



014-1084-010

## Art. 014-1084-100

### Grease digital meter nozzle

Composed by:

Digital meter 4 digits

Triple-swivelling joint

Rigid end + 4-jaws coupling

Not approved for public use

| Technical data         |        | 014-1084-000 | 014-1084-010 | 014-1084-100 |
|------------------------|--------|--------------|--------------|--------------|
| Flow rate              | gpm    | 0,003-0,66   | 0,003-0,66   | 0,003-0,66   |
| Inlet connection       | BSP    | F 1/8"G      | F 1/8"G      | F 1/4"G      |
| Outlet connection      | BSP    | F 1/8"G      | F 1/8"G      | F 10X1       |
| Max working pressure   | bar    | 500          | 500          | 500          |
| Burst pressure         | bar    | 1000         | 1000         | 1000         |
| Batch meter            | cifre  | 4            | -            | 4            |
| Totalizing meter in kg | cifre  | 4            | -            | 4            |
| Working temperature    | max C° | 60°          | 60°          | 60°          |
| Battery life           | mesi   | 24           | 24           | 24           |



014-1084-100

## Art. 014-1042-000

### Pneumatic nozzle for grease R=50:1

### 500 cc with rigid pipe and jaws coupling

Suitable for Ø 52 mm 400 g cartridge

It is suitable for the distribution at high pressure of all kinds of grease.

The operating pressure for the grease pumps

may vary between a minimum of 3.5 bar and a maximum of 8.5 bar

| Technical data                 |         | 014-1042-000 |
|--------------------------------|---------|--------------|
| Flow rate                      | g/ciclo | 0,68         |
| Compression ratio              | bar     | 50:1         |
| Air consumption                | l/min   | 130          |
| Air inlet connection           | BSP     | F 1/4"G      |
| Grease outlet connection       | M       | F 10x1       |
| Grease delivery capacity 6 bar | g/min   | 1500         |
| Noise level                    | dB      | 80           |
| Tank capacity                  | g       | 500          |
| Inside diameter of chamber     | mm      | 54           |
| For cartridge ø 52mm           | g       | 400          |



014-1042-000